



Cartridge Filter **CF SERIES**

COMPACT AND LIGHTWEIGHT
For residential pools and spas



UV resistant tank

Max Operating Pressure

250kPa/36psi(2.5bar)

Max Temperature

40°C (104°F)

Pool & Spa Equipment

The CF Series Cartridge Filter

comes with a UV resistant tank and a heavy duty ring-lock lid which allows easy cleaning and replacement of the cartridge element. A screw type air bleed valve releases trapped air inside the filter tank. The high quality oil-filled pressure gauge provides an easy overview of the operating pressure.

Product Information:

Code	Model	Filter Area (m ²)	Valve Connections	Max Flow Rate	A mm	B mm	C mm
88060101	CF25	2.25	1.5" / 50mm	92lpm 5.5m ³ /h	445	387	225
88060102	CF50	4.63	1.5" / 50mm	190lpm 11.4m ³ /h	625	567	225
88060103	CF75	7.00	1.5" / 50mm	283lpm 17.0m ³ /h	805	747	225
88060104	CF100	9.40	2.0" / 63mm	382lpm 22.9m ³ /h	985	927	225
88060105	CF150	13.72	2.0" / 63mm	555lpm 33.4m ³ /h	1165	1107	225
88060106	CF200	16.82	2.0" / 63mm	680lpm 40.9m ³ /h	1345	1287	225




The CF Series Filter is equipped with:

1. universal standard of union connection
2. pressure gauge
3. cartridge filter element

Cartridge Filter Element:

Code	Model	D mm	E mm	Micron μ m	Fold Number
88270101	CF25-CE	Ø183	184.5	≥15	150
88270102	CF50-CE	Ø183	364.5	≥15	150
88270103	CF75-CE	Ø183	544.5	≥15	150
88270104	CF100-CE	Ø183	724.5	≥15	150
88270105	CF150-CE	Ø183	904.5	≥15	175
88270106	CF200-CE	Ø183	544.5 x 2	≥15	180



45 - 47 Paul Matthews Road, Albany Auckland New Zealand

Phone: (09) 4151499 Email: filtermaster@xtra.co.nz

Web: www.filtermaster.co.nz

FULLY NEW ZEALAND OWNED AND OPERATED